Connector



DIP PLUG Series

KLS1-205 DIP PLUG 2.54mm(0.100")/DC4(F.D)扁平电缆连接器

Electrical Characteristics:


Current Rating: 1 AMP Insulator Resistance: $5000 \text{M}\Omega \text{min.}$ at DC 500 V Contact Resistance: $20 \text{m}\Omega \text{max.}$ at DC 100 mA Operating Temperature: $-45^{\circ}\text{C} \sim +105^{\circ}\text{C}$

Material:

Housing:30% Glass filled PBT UL94V-0
Contacts: Brass or Phosphor Bronze
Plating: Selective gold plated:gold plated on mating
area and nickel pleated on wire cutting area
Gold plated:2u". over 50u" nickel
Tin plated:100u". over 50u" nickel
Cable:1.27mm(0.050") pitch flat cable

Features:


- * Fast connection of flat cable to PC board.
- * Recommended 28AWG 1.27mm(0.05") fiat cable.
- * Plug directly into 2.54mmX2.54mm PC board.















Position	Α	В
06	12.82	5.08
08	15.36	7.62
10	17.90	10.16
14	22.98	15.24
16	25.52	17.78
20	30.60	22.86
24	35.68	27.94
26	38.22	30.48
30	43.30	35.56
34	48.38	40.64
40	56.00	48.26
50	68.70	60.96

Dimension





ORDER INFORMATION

