

TERMINAL BLOCK Connector

KLS electronic
www.cnkls.com

Barrier Series




KLS2-35C-8.25 Series

Electrical

Voltage rating : 300V
Current rating : 15A
Wire range : 14-22AWG
Operation temperature : -40°C to +105°C
Torque : 4kg/cm
Insulation Resistance: 500MΩ/DC500V
Withstanding Voltage: AC2000V/Min

MATERIAL

Housing : PA 66 UL94V-0
Terminal : Brass 0.8t, Tin plated
Screws : M3 Steel, Nickel Plated



ORDER INFORMATION

Product NO.: KLS2-35C-8.25 XXP B

Pos. NO. _____
Series No. _____
Pitch 8.25=8.25mm _____

A=Mount Ends B=Barrier Ends
Pin Number _____

TERMINAL BLOCK Connector

KLS electronic
www.cnkls.com

Barrier Series

KLS2-35C-8.25 Series

Electrical



Voltage rating : 300V
Current rating : 15A
Wire range : 14-22AWG
Operation temperature : -40°C to +105°C
Torque : 4kg/cm
Insulation Resistance: 500MΩ/DC500V
Withstanding Voltage: AC2000V/Min

MATERIAL

Housing : PA 66 UL94V-0
Terminal : Brass 0.8t, Tin plated
Screws : M3 Steel, Nickel Plated



II



ORDER INFORMATION

Product NO.: KLS2-35C-8.25 XXP A

Pos. NO.

Series No.

Pitch 8.25=8.25mm

A=Mount Ends B=Barrier Ends

Pin Number