

Switch

KLSelectronic
www.cnkls.com



Slide Switch Series

KLS7-SK03-14D10 (1P4T) Slide Switch Series




SPECIFICATIONS

Rating: 0.3A 50VDC
Contact Resistance: 30mΩ Max
Insulation Resistance: 500VDC 100MΩ Min
Dielectric Strength: 500V AC 1 Minute
Operating Force: 100gf~800gf
Electrical Life : 10,000 cycles


VII



SCHEMATIC



P.C.B. HOLE DETAIL



ORDER INFORMATION

KLS7-SK03 - 1 4 D 10 - X X - X

Part Number

Slide Switch Type

Pole

Throw

Operating Force

Knobe Height

Sequential No.

Travelling					
C	D	E	F	G	H
1.5	2.0	2.5	3.0	3.5	4.0
I	J	K	L	N	P
4.5	5.0	5.5	6.0	7.0	8.0

Knob Type					
RG	G	TG	VG	EG	CG

All specification & dimensions are subject to change, please call your nearest KLS sales representative for update information



Switch

Slide Switch Series




KLS7-SK04-14D02 (1P4T) Slide Switch Series

SPECIFICATIONS


Rating: 0.3A 50VDC
Contact Resistance: 30mΩ Max
Insulation Resistance: 500VDC 100MΩ Min
Dielectric Strength: 500V AC 1 Minute
Operating Force: 100gf~800gf
Electrical Life : 10,000 cycles



SCHEMATIC



P.C.B. HOLE DETAIL



ORDER INFORMATION

KLS7-SK04 - 1 4 D 02 - X X - X

Part Number

Slide Switch Type

Pole

Throw

Travelling					
C	D	E	F	G	H
1.5	2.0	2.5	3.0	3.5	4.0
I	J	K	L	N	P
4.5	5.0	5.5	6.0	7.0	8.0

Operating Force

Knobe Height

Sequential No.

